

Apparecchio a parete per esterno (IP65) a LED o con attacco E27 che consente di montare lampadine LED. Disponibile nella versione monoemissione e biemissione. Struttura in pressofusione di alluminio verniciato con polveri poliestere ad elevata resistenza ai raggi ultravioletti e alla corrosione, diffusore in vetro temperato. Proposta in tre finiture (bianco, grigio e antracite). Versione LED con fascio di luce 120°, alimentatore LED integrato e con due temperature colore selezionabili tramite switch (3000K-4000K). Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticondensa

LED outdoor (IP65) wall luminaire or with E27 lamp holder that allows mounting the LED lamp. Available in direct and direct/indirect light emission. Die-cast aluminum painted with polyester powders body with a very compact and elegant line, with high resistance to UV rays and corrosion, tempered glass diffuser. Three finishes (white, grey and anthracite). LED version with light beam 120°, integrated LED driver and two gradations selectable by switch (3000K-4000K). IP68 linear connectors for moisture protection and anti-condensation linear joints are available.

# WILLY



New



# WILLY



New

## MONOEMISSIONE DIRECT LIGHT



**LED**
**CRI≥80**
**IP65**

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>WIL001XX</b>	3000K-4000K	700	7W	250 x 60 x 60





## BIEMISSIONE DIRECT-INDIRECT LIGHT



**LED**
**CRI≥80**
**IP65**

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>WIL002XX</b>	3000K-4000K	1400	15W	250 x 60 x 60





## BIEMISSIONE DIRECT-INDIRECT LIGHT



**IP54**

Codice Code		Potenza Wattage	Dimensioni mm Dimensions mm
<b>WIL003XX</b>	E27	2x15W LED max	380 x 85 x 75



Switch per temperatura colore (3000K-4000K)  
Colour temperature switch (3000K-4000K)

3000K ↔ 4000K

### Finiture Finishes



B



GR



AN

### Accessori Accessories



connessione IP68  
IP68 connection

p.897